

SAFETY DATA SHEET

Based on Directive 2001/58/EC of the Commission of the European Communities

SOUDAFOAM 1K B3

1. Identification of the substance/preparation and of the company/undertaking

1.1 Identification of the substance or preparation:

- Not applicable

1.2 Use of the substance or the preparation:

Isolation

1.3 Company/undertaking identification:

SOUDAL N.V.
Everdongenlaan 18-20
B-2300 Turnhout
Tel. : +32 14 42 42 31
Fax : +32 14 44 39 71

1.4 Telephone number for emergency:

+32 14 58 45 45
Brandweerinformatiecentrum voor gevaarlijke stoffen (B.I.G.)
Technische Schoolstraat 43 A, B-2440 Geel

2. Composition/information on ingredients

| Hazardous ingredients | CAS No. EINECS No. | Conc. in % | Hazard symbol | Risks (R-phrases) |
|-----------------------------------------------------------------------------------------------|-------------------------|---------------|------------------|-----------------------|
| polymethylenepolyphenylisocyanate | 9016-87-9 - | > 25 | Xn | 20-36/37/38-42/43 (1) |
| tris(2-chloro-1-methylethyl)phosphate | 13674-84-5 237-158-7 | < 25 | - | 52/53 (1) |
| alpha, alpha', alpha''-1,2,3-propanetriyltris(omega-hydroxy-)poly[oxy(methyl-1,2-ethanediyl)] | 25791-96-2 500-044-5 | < 25 | Xn | 22 (1) |
| isobutane | 75-28-5 200-857-2 | 1 - 10 | F+ | 12 (1) |
| dimethyl ether | 115-10-6 204-065-8 | 1 - 5 | F+ | 12 (1) |
| propane | 74-98-6 200-827-9 | 1 - 5 | F+ | 12 (1) |

(1) For R-phrases in full: see heading 16

3. Hazards identification

- Extremely flammable
- Harmful by inhalation
- Irritating to eyes, respiratory system and skin
- May cause sensitization by inhalation and skin contact

Printing date : 04-2003 1/11
Compiled by : Brandweerinformatiecentrum voor Gevaarlijke Stoffen vzw (BIG)
Technische Schoolstraat 43 A, B-2440 Geel
☎ +32 14 58 45 47 http://www.big.be E-mail: info@big.be

MSDS established : 05-04-2002 Revisiondate : 19-12-2002
Reference number : BIG\32972GB Revision number : 004
Reason for revision : Directive 2001/58/EC

SOUDAFOAM 1K B3

4. First aid measures

- 4.1 Eye contact:**
- Rinse immediately with plenty of water
 - Seek medical advice
- 4.2 Skin contact:**
- Wash immediately with lots of water
 - If irritation persists: seek medical advice
- 4.3 After inhalation:**
- Remove the victim into fresh air
 - Seek medical advice
- 4.4 After ingestion:**
- Never give water to an unconscious person
 - Seek medical advice

5. Fire-fighting measures

- 5.1 Suitable extinguishing media:**
- Quantities of water
 - Polyvalent foam
 - BC powder
 - Carbon dioxide
- 5.2 Unsuitable extinguishing media:**
- None
- 5.3 Special exposure hazards:**
- On heating: release of toxic/combustible gases/vapours: phosphorus oxides, nitrous vapours, hydrogen chloride, carbon monoxide and carbon dioxide
 - Gas/vapour spreads at floor level: ignition hazard
 - Vapour-air mixture is flammable/explosive within the explosion limits
 - Aerosol may explode under the effect of heat
- 5.4 Instructions:**
- Dilute toxic gases with water spray
 - Do not move the load if exposed to heat
- 5.5 Special protective equipment for firefighters:**
- Heat/fire exposure: compressed air/oxygen apparatus

6. Accidental release measures

- 6.1 Personal protection/precautions:**
- See heading 8.1/8.3/10.3
- 6.2 Environmental precautions:**
- Use appropriate containment to avoid environmental contamination
- 6.3 Methods of cleaning up:**
- Allow product to solidify and remove it by mechanical means
 - Remove uncured foam with acetone

SOUDAFOAM 1K B3

7. Handling and storage

7.1 Handling:

- Observe very strict hygiene - avoid contact
- In case of insufficient ventilation: keep naked flames/sparks away
- Remove contaminated clothing immediately/reinigen

7.2 Storage:

- Keep out of direct sunlight
- Keep away from: heat sources, ignition sources, acids, bases

| | | |
|-------------------------|---------------------|------|
| Storage temperature | : < 50 | °C |
| Quantity limit | : N.D. | kg |
| Storage life | : 365 | days |
| Materials for packaging | : | |
| - suitable | : aerosol dispenser | |

7.3 Specific uses:

- See information supplied by the manufacturer

8. Exposure controls/Personal protection

8.1 Exposure limit values:

POLYMETHYLENEPOLYPHENYLISOCYANATE:

| | | | | |
|-----------------|---------------|-------------------|---|-----|
| TLV-TWA | : - | mg/m ³ | - | ppm |
| TLV-STEL | : - | mg/m ³ | - | ppm |
| TLV-Ceiling | : - | mg/m ³ | - | ppm |
| MEL-LTEL | : 0.02 (-NCO) | mg/m ³ | - | ppm |
| MEL-STEL | : 0.07 (-NCO) | mg/m ³ | - | ppm |
| MAK | : - | mg/m ³ | - | ppm |
| TRK | : - | mg/m ³ | - | ppm |
| MAC-TGG 8 h | : - | mg/m ³ | | |
| MAC-TGG 15 min. | : - | mg/m ³ | | |
| MAC-Ceiling | : - | mg/m ³ | | |
| VME-8 h | : - | mg/m ³ | - | ppm |
| VLE-15 min. | : - | mg/m ³ | - | ppm |
| GWBB-8 h | : - | mg/m ³ | - | ppm |
| GWK-15 min. | : - | mg/m ³ | - | ppm |
| Momentary value | : - | mg/m ³ | - | ppm |
| EC | : - | mg/m ³ | - | ppm |
| EC-STEL | : - | mg/m ³ | - | ppm |

SOUDAFOAM 1K B3

ISOBUTANE :

| | | | | |
|-----------------|--------|-------------------|------|-----|
| TLV-TWA | : - | mg/m ³ | - | ppm |
| TLV-STEL | : - | mg/m ³ | - | ppm |
| TLV-Ceiling | : - | mg/m ³ | - | ppm |
| OES-LTEL | : - | mg/m ³ | - | ppm |
| OES-STEL | : - | mg/m ³ | - | ppm |
| MAK | : 2400 | mg/m ³ | 1000 | ppm |
| TRK | : - | mg/m ³ | - | ppm |
| MAC-TGG 8 h | : - | mg/m ³ | | |
| MAC-TGG 15 min. | : - | mg/m ³ | | |
| MAC-Ceiling | : - | mg/m ³ | | |
| VME-8 h | : - | mg/m ³ | - | ppm |
| VLE-15 min. | : - | mg/m ³ | - | ppm |
| GWBB-8 h | : - | mg/m ³ | - | ppm |
| GWK-15 min. | : - | mg/m ³ | - | ppm |
| Momentary value | : - | mg/m ³ | - | ppm |
| EC | : - | mg/m ³ | - | ppm |
| EC-STEL | : - | mg/m ³ | - | ppm |

DIMETHYL ETHER :

| | | | | |
|-----------------|--------|-------------------|------|-----|
| TLV-TWA | : - | mg/m ³ | - | ppm |
| TLV-STEL | : - | mg/m ³ | - | ppm |
| TLV-Ceiling | : - | mg/m ³ | - | ppm |
| OES-LTEL | : - | mg/m ³ | 400 | ppm |
| OES-STEL | : - | mg/m ³ | 500 | ppm |
| MAK | : 1900 | mg/m ³ | 1000 | ppm |
| TRK | : - | mg/m ³ | - | ppm |
| MAC-TGG 8 h | : 950 | mg/m ³ | | |
| MAC-TGG 15 min. | : 1500 | mg/m ³ | | |
| MAC-Ceiling | : - | mg/m ³ | | |
| VME-8 h | : - | mg/m ³ | - | ppm |
| VLE-15 min. | : - | mg/m ³ | - | ppm |
| GWBB-8 h | : - | mg/m ³ | - | ppm |
| GWK-15 min. | : - | mg/m ³ | - | ppm |
| Momentary value | : - | mg/m ³ | - | ppm |
| EC | : 1920 | mg/m ³ | 1000 | ppm |
| EC-STEL | : - | mg/m ³ | - | ppm |

PROPANE :

| | | | | |
|-----------------|--------|-------------------|------|-----|
| TLV-TWA | : - | mg/m ³ | 2500 | ppm |
| TLV-STEL | : - | mg/m ³ | - | ppm |
| TLV-Ceiling | : - | mg/m ³ | - | ppm |
| OES-LTEL | : - | mg/m ³ | - | ppm |
| OES-STEL | : - | mg/m ³ | - | ppm |
| MAK | : 1800 | mg/m ³ | 1000 | ppm |
| TRK | : - | mg/m ³ | - | ppm |
| MAC-TGG 8 h | : - | mg/m ³ | | |
| MAC-TGG 15 min. | : - | mg/m ³ | | |
| MAC-Ceiling | : - | mg/m ³ | | |
| VME-8 h | : - | mg/m ³ | - | ppm |
| VLE-15 min. | : - | mg/m ³ | - | ppm |
| GWBB-8 h | : - | mg/m ³ | - | ppm |
| GWK-15 min. | : - | mg/m ³ | - | ppm |
| Momentary value | : - | mg/m ³ | - | ppm |
| EC | : - | mg/m ³ | - | ppm |
| EC-STEL | : - | mg/m ³ | - | ppm |

SOUDAFOAM 1K B3

8.2 Exposure controls:

8.2.1 Occupational exposure controls:

- Use only in well ventilated area

8.2.2 Environmental exposure controls: see heading 13

8.3 Personal protection:

8.3.1 respiratory protection:

- In case of insufficient ventilation: gas mask with filter type A

8.3.2 hand protection:

- Gloves

8.3.3 eye protection:

- Protective goggles

8.3.4 skin protection:

- Protective clothing

9. Physical and chemical properties

9.1 General information:

| | |
|----------------------|----------------------|
| Appearance (at 20°C) | : Aerosol |
| Odour | : Characteristic |
| Colour | : Variable in colour |

9.2 Important health, safety and environmental information:

| | | |
|---------------------------------------|-------------------------------------------|------|
| pH value | : N.D. | |
| Boiling point/boiling range | : N.D. | °C |
| Flashpoint | : Contains extremely flammable components | |
| Explosion limits | : N.D. | vol% |
| Vapour pressure (at 20°C) | : N.D. | hPa |
| Vapour pressure (at 50°C) | : N.D. | hPa |
| Relative density (at 20°C) | : N.D. | |
| Water solubility | : Insoluble | |
| Soluble in | : N.D. | |
| Relative vapour density | : N.D. | |
| Viscosity | : N.D. | Pa.s |
| Partition coefficient n-octanol/water | : N.D. | |
| Evaporation rate | | |
| ratio to butyl acetate | : N.D. | |
| ratio to ether | : N.D. | |

9.3 Other information:

| | | |
|-----------------------------|--------|------------------|
| Melting point/melting range | : N.D. | °C |
| Auto-ignition point | : N.D. | °C |
| Saturation concentration | : N.D. | g/m ³ |

SOUDAFOAM 1K B3

10. Stability and reactivity

10.1 Conditions to avoid/reactivity:

- Unstable on exposure to heat

10.2 Materials to avoid:

- Heat sources, ignition sources, acids, bases

10.3 Hazardous decomposition products:

- May polymerize on exposure to temperature rise
- On heating: release of toxic/combustible gases/vapours: hydrogen cyanide
- On heating: release of toxic/combustible gases/vapours: phosphorus oxides, nitrous vapours, hydrogen chloride, carbon monoxide and carbon dioxide
- May polymerize with many compounds e.g.: (strong) bases and amines
- Reacts violently with (some) acids/bases

11. Toxicological information

11.1 Acute toxicity:

POLYMETHYLENEPOLYPHENYLISOCYANATE:

| | | |
|---------------------|-----------|----------|
| LD50 oral rat | : > 10000 | mg/kg |
| LD50 dermal rabbit | : N.D. | mg/kg |
| LD50 dermal rabbit | : > 5000 | mg/kg |
| LC50 inhalation rat | : N.D. | mg/l/4 h |
| LC50 inhalation rat | : N.D. | ppm/4 h |

TRIS(2-CHLORO-1-METHYLETHYL)PHOSPHATE:

| | | |
|---------------------|----------|----------|
| LD50 oral rat | : 3600 | mg/kg |
| LD50 dermal rabbit | : > 2000 | mg/kg |
| LD50 dermal rabbit | : > 2000 | mg/kg |
| LC50 inhalation rat | : > 5 | mg/l/4 h |
| LC50 inhalation rat | : N.D. | ppm/4 h |

alpha,alpha',alpha''-1,2,3-PROPANETRIYL-tris(omega-HYDROXY-) POLY[OXY(METHYL-1,2-ETHANEDIYL)]:

| | | |
|---------------------|-------------|----------|
| LD50 oral rat | : 1500/2000 | mg/kg |
| LD50 dermal rabbit | : N.D. | mg/kg |
| LD50 dermal rabbit | : > 2000 | mg/kg |
| LC50 inhalation rat | : N.D. | mg/l/4 h |
| LC50 inhalation rat | : N.D. | ppm/4 h |

ISOBUTANE:

| | | |
|---------------------|--------|----------|
| LD50 oral rat | : N.D. | mg/kg |
| LD50 dermal rabbit | : N.D. | mg/kg |
| LD50 dermal rabbit | : N.D. | mg/kg |
| LC50 inhalation rat | : 658 | mg/l/4 h |
| LC50 inhalation rat | : N.D. | ppm/4 h |

PROPANE:

| | | |
|---------------------|----------|----------|
| LD50 oral rat | : N.D. | mg/kg |
| LD50 dermal rabbit | : N.D. | mg/kg |
| LD50 dermal rabbit | : N.D. | mg/kg |
| LC50 inhalation rat | : 513 | mg/l/4 h |
| LC50 inhalation rat | : 280000 | ppm/4 h |

11.2 Chronic toxicity:

POLYMETHYLENENPOLYPHENYLISOCYANATE:

EC carc. cat. : not listed
EC muta. cat. : not listed
EC repr. cat. : not listed

Carcinogenicity (TLV) : not listed
Carcinogenicity (MAC) : not listed
Carcinogenicity (VME) : not listed
Carcinogenicity (GWBB) : not listed

Carcinogenicity (MAK) : 3B
Mutagenicity (MAK) : not listed
Teratogenicity (MAK) : -

IARC classification : 3

DIMETHYL ETHER:

EC carc. cat. : not listed
EC muta. cat. : not listed
EC repr. cat. : not listed

Carcinogenicity (TLV) : not listed
Carcinogenicity (MAC) : not listed
Carcinogenicity (VME) : not listed
Carcinogenicity (GWBB) : not listed

Carcinogenicity (MAK) : not listed
Mutagenicity (MAK) : not listed
Teratogenicity (MAK) : D

IARC classification : not listed

11.3 Routes of exposure: inhalation, eyes and skin

11.4 Acute effects/symptoms (upon overexposure) :

AFTER INHALATION:

- Dry/sore throat
- Coughing
- Irritation of the respiratory tract
- Irritation of the nasal mucous membranes
- Runny nose

FOLLOWING SYMPTOMS MAY APPEAR LATER:

- Inflammation of the respiratory tract
- Risk of lung oedema
- Respiratory difficulties

AFTER SKIN CONTACT:

- Tingling/irritation of the skin

AFTER EYE CONTACT:

- Irritation of the eye tissue
- Lacrimation

11.5 Chronic effects:

- May cause sensitization by skin contact
- May cause sensitization by inhalation
- Contains substance with uncertain carcinogenic properties (polymethylenepolyphenylisocyanate)

ON CONTINUOUS EXPOSURE/CONTACT:

- Body temperature rise
- Tremor
- Feeling of weakness
- Headache
- Skin rash/inflammation
- May stain the skin
- Dry skin
- Risk of pneumonia

12. Ecological information

12.1 Ecotoxicity:

TRIS(2-CHLORO-1-METHYLETYL)PHOSPHATE:

- LC50 (96 h) : 56.2 mg/l (BRACHYDANIO RERIO)
- EC50 (48 h) : 65/335 mg/l (DAPHNIA MAGNA)
- EC50 (48 h) : 57/97 mg/l (SELENASTRUM CAPRICORNUTUM)

12.2 Mobility:

- Volatile organic compounds (VOC): 18 %
- For other physicochemical properties see section 9

12.3 Persistence and degradability:

- biodegradation BOD₅ : N.D. % ThOD
- water : No data available
- soil : T ½: N.D. days

12.4 Bioaccumulative potential:

- log P_{ow} : N.D.
- BCF : N.D.

12.5 Other adverse effects:

- WGK : 1 (classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 17 May 1999)
- Effect on the ozone layer : Not dangerous for the ozone layer (1999/45/EC)
- Greenhouse effect : No data available
- Effect on waste water purification : No data available

13. Disposal considerations

13.1 Provisions relating to waste:

- Waste material code (91/689/EEC, Council Decision 2001/118/EC, O.J. L47 of 16/2/2001): 08 05 01 (waste isocyanates)
- Waste material code (Flanders): 015; 651
- Hazardous waste (91/689/EEC)


13.2 Disposal methods:

- Specific treatment

13.3 Packaging:

- Waste material code packaging (91/689/EEC, Council Decision 2001/118/EC, O.J. L47 of 16/2/2001): 15 01 10 (packaging containing residues of or contaminated by dangerous substances)

14. Transport information



14.1 Classification of the substance in compliance with UN Recommendations
 UN-number : 1950
 CLASS : 2.2
 SUB RISKS : -
 PACKING : -
 PROPER SHIPPING NAME :
 UN 1950, Aerosols

14.2 ADR (transport by road)
 CLASS : 2
 CLASSIFICATION CODE : 5 A
 DANGER LABEL TANKS : -
 DANGER LABEL PACKAGES : 2.2

14.3 RID (transport by rail)
 CLASS : 2
 CLASSIFICATION CODE : 5 A
 DANGER LABEL TANKS : -
 DANGER LABEL PACKAGES : 2.2

14.4 ADNR (transport by inland waterways)
 CLASS : 2
 CLASSIFICATION CODE : 5 A
 DANGER LABEL TANKS : -
 DANGER LABEL PACKAGES : 2.2

14.5 IMDG (maritime transport)
 CLASS : 2.2
 SUB RISKS : -
 PACKING : -
 MFAG : -
 EMS : 2-13
 MARINE POLLUTANT : -

14.6 ICAO (air transport)
 CLASS : 2.1
 SUB RISKS : -
 PACKING : -
 PACKING INSTRUCTIONS PASSENGER AIRCRAFT :
 PACKING INSTRUCTIONS CARGO AIRCRAFT :

14.7 Special precautions in connection with transport : none

14.8 Limited quantities (LQ) :

When substances and their packaging meet the conditions established by ADR/RID/ADNR in chapter 3.4, **only** the following prescriptions shall be complied with:
 each package shall display a diamond-shaped figure with the following inscription:
 - 'UN 1950'
 or, in the case of different goods with different identification numbers within a single package:
 - the letters 'LQ'

SOUDAFOAM 1K B3

15. Regulatory information

Labelling in accordance with EC directives 67/548/EEC and 1999/45/EC (**: see heading 16)



Extremely flammable



Harmful

Contains : polymethylenepolyphenylisocyanate

R20 : Harmful by inhalation
R36/37/38 : Irritating to eyes, respiratory system and skin
R42/43 : May cause sensitization by inhalation and skin contact

S23 : Do not breathe spray
S36/37/39 : Wear suitable protective clothing gloves, and eye/face protection
S38 : In case of insufficient ventilation, wear respiratory equipment
S45 : In case of accident or if you feel unwell, seek medical advice (show the label where possible)
S51 : Use only in well ventilated area

Keep away from sources of ignition - No smoking.
Keep out of reach of children.
Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C.
Do not pierce or burn after use.
Do not spray on a naked flame or any incandescent material

Contains isocyanates. See information supplied by the manufacturer.

SOUDAFOAM 1K B3

16. Other information

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

N.A. = NOT APPLICABLE
N.D. = NOT DETERMINED
***** = INTERNAL CLASSIFICATION

(**) Labelling:

The labelling of the substance described in this MSDS complies with the provisions of Directive 1999/45/EC of 31 May 1999, published in the Official Journal of the European Communities L 200 of 30/07/1999. This Directive replaces Directive 88/379/EEC of 7 June 1988, published in the Official Journal of the European Communities L 187 of 16/07/1988.

Member States shall apply the laws, regulations and administrative provisions referred to in article 22 of this Directive:

- (a) to preparations not within the scope of Directive 91/414/EEC or Directive 98/8/EC as from 30 July 2002; and
- (b) to preparations within the scope of Directive 91/414/EEC or Directive 98/8/EC as from 30 July 2004.

Full text of any R-phrases referred to under heading 2:

R12 : Extremely flammable
R20 : Harmful by inhalation
R22 : Harmful if swallowed
R36/37/38 : Irritating to eyes, respiratory system and skin
R42/43 : May cause sensitization by inhalation and skin contact
R52/53 : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Exposure limits:

TLV : Threshold Limit Value - ACGIH US 2000
OES : Occupational Exposure Standards - United Kingdom 1999
MEL : Maximum Exposure Limits - United Kingdom 1999
MAK : Maximale Arbeitsplatzkonzentrationen - Germany 2001
TRK : Technische Richtkonzentrationen - Germany 2001
MAC : Maximale aanvaarde concentratie - the Netherlands 2002
VME : Valeurs limites de Moyenne d'Exposition - France 1999
VLE : Valeurs limites d'Exposition à court terme - France 1999
GWBB : Grenswaarde beroepsmatige blootstelling - Belgium 1998
GWK : Grenswaarde kortstondige blootstelling - Belgium 1998
EC : Indicative occupational exposure limit values - directive 2000/39/EC

I : Inhalable fraction = **T** : Total dust = **E** : Einatembarer Aerosolanteil
R : Respirable fraction = **A** : Alveolengängiger Aerosolanteil/Alveolar dust
C : Ceiling limit

| | | | | | |
|------------|-----------|------------|-------------------|------------|--------|
| a: | aerosol | r: | rook/Rauch | (fume) | |
| d: | damp | (vapour) | st: | stof/Staub | (dust) |
| du: | dust | ve: | vezel | (fibre) | |
| fa: | Faser | (fibre) | va: | vapour | |
| fi: | fibre | om: | oil mist | | |
| fu: | fume | on: | olienevel/Ölnebel | (oil mist) | |
| p: | poussière | (dust) | part: | particles | |

Chronic toxicity:

K : List of the carcinogenic substances and processes - the Netherlands 2002